

*“Speed, Flexibility, Dependable Performance”*

ST-1322/2  
STB-1432/2

# Double Chamber Forced Air Tunnels



MADE IN U.S.A

Distributed by:



**TEXWRAP**<sup>®</sup>  
525 Vossbrink Drive · Washington, MO 63090  
Ph (636)239-7424 · Fax (636) 239-7322  
sales@texwrap.com · www.texwrap.com

## Features, Functions & Benefits

- Continuous duty industrial grade blower motor
- Air velocity control
- Top/bottom adjustable air control dampers for controlled shrink results
- Easy to read L.E.D. display
- Cool-Touch energy efficient design
- AC motor with variable speed control for conveyor speed
- Air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink
- Audible high heat alarm and high heat limit thermostat
- Stainless steel mesh belt
- Durable powder coat finish
- Various Belt options available

| Specifications:  | ST-1322/2                 | STB-1432/2                | ST-1322/2                   | STB-1432/2              |
|------------------|---------------------------|---------------------------|-----------------------------|-------------------------|
| Opening:         | 13" H x 22"W              | 14"H x 32"W               | A = 85"                     | 111"                    |
| Electrical:      | 240V, 65 amp, 3 phase     | 480V, 67 amp, 3 phase     | B = 34.6"                   | 42.25"                  |
| Heaters:         | 6 flange cal-rod types    | 6 flange cal-rod types    | C = 132.8"                  | 158.8"                  |
| Conveyor Height: | Adj. from 33" to 37-1/2"H | Adj. from 30-1/2" to 36"H | D = 79" min.<br>(allow 96") | 80" min.<br>(allow 96") |
| Conveyor Width:  | 15"                       | 24"                       | E = 30" min.                | 30-1/2" min             |
| Chamber Length:  | 85"                       | 111"                      | F = 44"                     | 54.5"                   |
| Conveyor Speed:  | 0-160 FPM                 | 0-160 FPM                 |                             |                         |
| Shipping Weight: | 1,820 lbs                 | 2,000 lbs                 |                             |                         |

