

STB-1322/3
STB-1432/3

Triple Chamber Forced Air Tunnels



MADE IN U.S.A

Distributed by:

Features, Functions & Benefits

- Continuous duty industrial grade blower motor
- Air velocity control
- Top/bottom adjustable air control dampers for controlled shrink results
- Easy to read L.E.D. display
- Cool-Touch energy efficient design
- AC motor with variable speed control for conveyor speed
- Air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink
- Audible high heat alarm and high heat limit thermostat
- Stainless steel mesh belt
- Durable powder coat finish
- Various Belt options available

Specifications: STB-1322/3

Opening:	13" H x 22"W
Electrical:	480V, 70 amp, 3 phase
Heaters:	9 flange cal-rod types
Conveyor Height:	Adj. from 31-1/2" to 37"H
Conveyor Width:	15"
Chamber Length:	127-1/2"
Conveyor Speed:	0-225 FPM
Shipping Weight:	2,500 lbs

STB-1432/3

Opening:	14"H x 32"W
Electrical:	480V, 99 amp, 3 phase
Heaters:	9 flange cal-rod types
Conveyor Height:	Adj. from 31-1/2" to 37"H
Conveyor Width:	24"
Chamber Length:	174"
Conveyor Speed:	0-225 FPM
Shipping Weight:	3,000 lbs

STB-1322/3 STB-1432/3

A =	127-1/2"	174"
B =	34-5/8"	44-1/2"
C =	177"	215"
D =	80" min. (allow 96")	81" min. (allow 96")
E =	31-1/2" min.	31-1/2"
F =	47"	57"

